



GENERATING SETS

WATER COOLED
 THREE PHASES
 50 HZ
 DIESEL

Service		Standby	Prime
Power	kVA	33	30
Power	kW	26,4	24
Rated Speed	r.p.m	1500	
Standart Voltage	V	400/230	
Rated At Power Factor	Cos Phi	0,8	

MAR-KIM Company with quality certification ISO 9001

MAR-KIM gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2005 normative: 1000 mbar, 25°C, 30% relative humidity.

G2 class load acceptance in accordance with ISO 8528-5:2013

MAR-KIM CHEMICALS CO.LTD.

KINONDONI TUNISIA ROAD. PLOT NO:137 DAR ES SALAM-TANZANIA

TEL : +2550786323584 | +255 0677 062 017 | +255 0677062024

info@markimgroup.co.tz | www.markimgenerator.com | instagram : markimperkinsgenerators



MP33

INDUSTRIAL RANGE

Perkins

SPECIFICATIONS



Engine



Alternator

Engine	Specifications
Rated Output	<i>kW</i> 24
Manufacturer	Perkins
Model	1103A-33G
Engine Type	4 Stroke - Diesel
Injection Type	Direct Injection
Aspiration Type	Naturally Aspirated
Number of cylinder	3 L
Bore and Stroke	<i>mm</i> 105x127
Displacement	<i>L</i> 3,3
Cooling System	Water Cooling
Heating Power	<i>Watt</i> 1000W
Fuel Consumption 50% PRP	<i>l/h</i> 4,06
Fuel Consumption 75% PRP	<i>l/h</i> 5,61
Fuel Consumption 100 % PRP	<i>l/h</i> 7,2
Fuel Consumption Standby	<i>l/h</i> 8,1
Lube oil consumption with full load	<i>[% fuel]</i> < 0,15
Total oil capacity including tubes, filters	<i>L</i> 8,3
Total coolant capacity	<i>L</i> 10,2
Governor	<i>Type</i> Mechanical/Electronic
Battery Capacity	<i>A</i> 60

Alternator	Specifications
Manufacturer	Maranello
Model	M33
Output Voltage	<i>V</i> 230/400
Frequency	<i>HZ</i> 50
Automatic Voltage Regulation	<i>±%</i> 1
Alternator Stand By Power	<i>kVA</i> 33
Alternator Continuous Power	<i>kVA</i> 30
Power Factor	<i>Cosφ</i> 0,8
Number of Wires	12
Winding	2/3
Protection Class	IP23 / H
Excitation System	Self-excited
AVR Model	SX460
Performance - PF 0,8 / %75 Load	<i>%</i> 88

Prime Power (PRP):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2005, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP.

Note: All data based on operation to ISO 3046/1, BS 5514 and DIN 6271 standard reference conditions

MAR-KIM CHEMICALS CO.LTD.

KINONDONI TUNISIA ROAD. PLOT NO:137 DAR ES SALAM-TANZANIA

TEL : +2550786323584 | +255 0677 062 017 | +255 0677062024

info@markimgroup.co.tz | www.markimgenerator.com | instagram : markimperkinsgenerators




MP33

INDUSTRIAL RANGE



DIMENSIONS



CANOPIED

LxWxH	mm	2225x970x2236
Weight	kg	1515
Fuel Tank	lt	1000

Sound Proof Canopy

- Special design for minimizing acoustic level.
- Galvanized steel construction further protected by polyester powder coat paint.
- Black finish stainless steel locks and hinges.
- Control panel viewing window in a lockable access door.
- Emergency stop push button (red) mounted on enclosure exterior.
- Lifting, drag and jacking points on base frame.
- Radiator fill via removable, flush mounted rain cap fitted with compression seal.
- Acoustic insulation with moisture-repellent and non-flammable material

MAR-KIM CHEMICALS CO.LTD.

KINONDONI TUNISIA ROAD. PLOT NO:137 DAR ES SALAM-TANZANIA

TEL : +2550786323584 | +255 0677 062 017 | +255 0677062024

info@markimgroup.co.tz | www.markimgenerator.com | instagram : markimperkinsgenerators



MP33

INDUSTRIAL RANGE

Perkins

CONTROL UNIT



Control Unit

DSE7410 - DEEP SEA

ATS unit with uninterrupted transfer	Internet Central Monitoring
AMF unit with uninterrupted transfer	SMS / E-mail message sending
Remote / Manuel start controller	Flexible with plug-in modules
Engine controller	Free PC software: Rainbow Plus
GSM-GPRS-GPS-Ethernet Port	Modbus RTU
8 configurable digital inputs	

ATS PANEL

MAR-KIM automatic transfer switches are reliable, rugged, versatile, and compact assemblies for transferring essential loads and electrical distribution systems from one power source to another. MAR-KIM's contactor-based transfer switch is rated 40–3600A and can be supplied in separate enclosures for standalone applications or can be supplied as an integral component. Contactors inside the ATS panels are well known and internationally recognized brands such as ABB, SCHNEIDER, HYUNDAI and ANDELI.



OPTIONAL EQUIPMENTS

Some Optional Equipments that MAR-KIM provides with Generator Sets;

- Medium voltage alternator,
- Remote radiator applications,
- Automatic fuel filling system,
- Fuel tank, oil pan, dashboard, alternator, coil heaters,
- Alternator with double AVR and PMG,
- Synchronization systems, The generator output breaker,
- Grid-generator transfer switches,
- Accordance with the specific volume of demand-insulated cabins,
- Seismic solutions,
- Trailer,
- Remote monitoring.
- SMPS 12/24V 10A

Control Panel

- Datakom D500
- Datakom D700
- ComAp AMF9
- ComAp AMF25

MAR-KIM CHEMICALS CO.LTD.

KINONDONI TUNISIA ROAD. PLOT NO:137 DAR ES SALAM-TANZANIA

TEL : +2550786323584 | +255 0677 062 017 | +255 0677062024

info@markimgroup.co.tz | www.markimgenerator.com | instagram : markimperkinsgenerators